

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-288271

(43)Date of publication of application : 31.10.1995

(51)Int.Cl.

H01L 21/66
G01R 31/28
G01R 31/28

(21)Application number : 06-080118

(71)Applicant : AGING TESUTA KAIHATSU KYODO KUMIAI

(22)Date of filing : 19.04.1994

(72)Inventor : NAKANO KATSUYOSHI
MIZUNO YUJI


(54) MEASURING ELECTRODE FOR INTEGRATED CIRCUIT

(57)Abstract

PURPOSE: To highly accurately bring contacts into contact with pads on a pattern relevant to an individual IC part by a method wherein a conductive and buffer member electrically connects base lands with opposed lands and moves a contact block in a contact direction toward a relay substrate.

CONSTITUTION: A conductive and buffer member 50 electrically connects base lands 32 relevant to a base 10 and a relay substrate 60 with opposite lands 61 for performing electrical connection and buffering.

The member 50 moves a contact block 20 provided on the base 10 toward the relay substrate 60 in a contact direction of pads 2 of an object to be examined. This movement regulates a position with fitting of a guide boss 72 for alignment provided on a support base 70, a guide boss 72 for alignment provided on the base 10 and a semicircular recess 11 provided on the base 10. Thus the contact block 20 can be highly accurately brought into contact with the pads 2 on a pattern concerned with an individual IC part.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision
of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]